

VMUS-4

KEY FEATURES:

- Produces Up to ~6.5g/hr.
- Wall mountable
- Flow meter is standard
- Integrated power-out plug
- Easy to install and operate
- Powder coated Al. cabinet

PRODUCT DESCRIPTION

The VMUS-4 is a wall mountable Ozone generator which produces up to 6.5g/hr of ozone @ 6 L/min of oxygen. Like all of our ozone generator, this generator utilizes our silent pulse injection corona discharge technology. This unit is typically used in water bottling plants, self contained site remediation systems, and air systems for commercial buildings.



AZCO INDUSTRIES LIMITED
ADVANCED OZONE SYSTEMS

SPECIFICATIONS

	VMUS-4 (E*)	VMUS-2 (E*)	SNOA-4 (E*)
General			
Voltage [VAC, 50/60Hz]	100-120 (200-240)		
Power Consumption [W]	100	60	180
Ambient Temperature [°C]	2 to 28		
Relative Humidity [%]	10-92 (non-condensing)		
Mass [Kg]	5.2 (7.1)	4.5 (5.6)	8.6 (9.9)
Dimensions [L x W x H] [mm] <small>1 mm = .039 inches</small>	435 x 260 x 135	430 x 260 x 112	435 x 260 x 135
Installation	Refer to AZCO's installation manual for specific product		
Warranty [Refer to AZCO warranty sheet]	3 Year		
Ozone			
Generation Process	Pulse, Corona Discharge		
Process Gas [bar] <small>1 bar = 14.5 psi</small>	Dry air or oxygen, free of dust and oil. Maximum pressure ± 0.36		
Production on Oxygen [Refer to Graph for more detail]	~ 6.5 g/hr @ 6 l/min	~5.0 g/hr @ 6 l/min	~4.0 g/hr @ 6 l/min on dry air
Options			
Internal Air Pump	O	O	O
Adjustable Output	O	O	O
Interlock	O	O	O
Flow Meter	S	S	S
Oxygen Ready	S	S	O
Vacuum Switch	O	O	O
Built-in Air Dryer	N/A	N/A	S
Safety			



E*: European Version, N/A: Not Applicable, O: Optional, S: Standard

